

Is your router giving you the red light?

Let us turn your frown upside down.

Follow these quick and easy steps to get your ZTE router set up and working for you at home.

## Step 1:

First check that your SIM card has been activated. Your FLTE router comes with a tri-SIM card (3 SIM sizes in 1).

Remove the SIM from the card and insert the correct sized SIM into your phone. If your SIM has been activated, you will receive a confirmation SMS.

\*NB: Don't throw away the plastic SIM adapter because you will need this to insert your SIM into your router later!



## Step 2:

Once your FLTE SIM card has been inserted into your phone, switch Airplane Mode ON and then OFF, to connect quickly.

\*NB: If you aren't picking up a connection, this means your SIM has not been activated yet. Remember, it can take between 1 to 2 working days to activate a new SIM. If it has been longer than 2 working days and your SIM card is still not activated, please contact the Mondo Customer Care team on 086 123 8888 or email us at customercare@mondo.co.za.

## Step 3:

If your SIM is activated, remove it from your phone and insert it into your router. Ensure the SIM card is the correct size and facing the correct direction (gold side facing upwards).

# Step 4:

You can set up your router by connecting the supplied LAN cable or through Wi–Fi using your PC or smartphone. If you are connecting via Wi–Fi, please select the ZTE 2.4G option from the available Wi–Fi connections on your PC or your smartphone.



Once connected, γou will need to open γour internet browser, such as Google Chrome or Microsoft Edge and enter the following IP Address in the address bar at the top of the page:

# 192.168.0.1

\*NB: This does not require Internet access.

## Step 5:

If you are asked for a password, please enter "admin" or the WLAN KEY which you can find on the label at the bottom of your router.

You will now see the router's home screen, where you will find 3 options:

- 1. Access Device
- 2. My Router
- 3. Net Surfing

\*NB: The UMTS or LTE button will be switched to OFF. Leave this OFF for now. Select Settings under Option 2 "Mγ Router."



Select the APN option.

Modify Login Password Logout
<u>6</u>
22.3

# Step 6:

Change the "Mode" setting from "Auto" to "Manual".

Current APN	MTN FLTE	
Mode	O Auto	

# Then scroll down to "Profile" and click the "Add New" button.

SSID 2.4GHz:ZTE_BA4512;SSID 5GH;	z:ZTE_BA4512;		No Service	odify Login Password Logout
APN				(6)
Current APN	MTN FLTE			
Mode	○ Auto	Manual		
Profile	MTN FLTE		Add New	
PDP Type	IPv4		~	

# Step 7:

Once Step 6 is done, you will need to fill in the following fields:

Profile Name: This can be any name of γour choice, e.g., Home Internet. APN: mγmtnhome (In lowercase) Authentication: NONE

\*NB: Your Username and Password tabs will remain blank.

Current APN	MTN Data	
Mode	O Auto O Manual	
Profile	MTN Data	
PDP Type	IPv4	
Profile Name *	MTN FLTE	
APN *	mymtnhome	
Authentication	NONE	
User Name		
Password		
		Alimity

#### Step 8:

Click the "Apply" button and then click the "Set as default" button.

Password	
	 Set as detmut

Once this is done, scroll back up and change the "Mode" setting from "Manual" back to "Auto".

Current APN	MTN FLTE		
Mode	Auto	O Manual	
Profile	MTN Data	~	

You can now return to the router's home screen and set the data connection button (UMTS) switch to ON. The red light on your router will turn green and you'll be connected to the network!

Happy surfing!